

Adawall Elastomeric Bitumen Sealant

Adawall Elastomeric Bitumen Sealant is a bituminous rubber sealant for sealing line drainage units and general jointing/waterproofing of construction products. It is in a ready to use cartridge and applied with a sealant gun.

CHARACTERISTICS

- Good adhesion on bituminous surfaces
- Easy to apply
- Can be applied on wet surfaces (even under water)
- Excellent slump resistance
- Accommodates movement up to 10%

APPLICATION EXAMPLES

- sealing of gaps and cracks and connection joints between drains
- sealing line drainage joints in concrete and steel drainage units

PACKAGING Cartridge of 310 ml

COLOURS Black

SHELF LIFE 1 year in unopened packaging in a cool and dry storage place.

TECHNICAL DATA

Base : Bituminous Elastomere

Consistency : Stable Paste

Curing system : Physical Drying

Skin formation : Surface Dryness after 20 min.

Curing rate : Does not apply

Hardness : Does not apply

Shrinkage : ca 11 %

Specific gravity : ca 1.25 g/ml

Temperature resistance : - 35°C until +130°C

Maximum allowed movement : 10 %

INSTRUCTIONS FOR USE

Surface preparation : Clean, free of dust and grease. May be wet.

Application method : Mastic gun

Application temperature : +1°C until + 30°C

Clean with : White Spirit immediately after application

JOINT DESIGN

Minimum width : 5 mm

Maximum width : 30 mm (3 pass method on larger joints)

Minimum depth : 5 mm

Recommendation : Joint Depth = Joint Width

SAFETY RECOMMENDATIONS Apply the usual industrial hygiene.