

Adawall Expanding Foam

SAFETY DATA SHEET

1.1 Identification of the substance or preparation:

- Not applicable

1.2 Use of the substance or the preparation:

Isolation

1.3 Company

2HK Solutions

Unit 6 Henfield Business Park

Westerleigh Road

Bristol BS362UP

0845 2238801

2 Composition on Ingredients

Hazardous ingredients	CAS No. EINECS No.	Conc in %	Hazard symbol	Risks (R-phrases)
Polymethylenepolyphenylisocyanate	9016-87-9	>25	Xn	2036/37/38-42/43
alpha, alpha, alpha 1,2,3, propanetriyltris (omega-hydroxy-)	25791-96-2	>25	Xn	22
poly(oxy(methyl-1-2-ethanediyl))	500-044-5			
isobutene	75-28-5	1-10	F+	12
	200-857-2			
dimethyl ether	115-10-6	1-5	F+	12
propane	74-98-6	1-5	F+	12
	200-827-9			

3 Hazard Identification

- Extremely flammable
- Harmful by inhalation
- Irritating to eyes, respiratory system and skin
 - May cause sensitization by inhalation and skin contact
-

4 First Aid Measures

4.1 Eye contact

- Rinse immediately with plenty of water
- Seek medical advice

4.2 Skin contact:

- Wash immediately with lots of water
 - If irritation persists: seek medical advice

4.3 After inhalation

- Remove the victim into fresh air
- Seek medical advice

4.4 After ingestion:

- Never give water to an unconscious person
 - Seek medical advice

5. Fire Fighting Measures**5.1 Suitable extinguishing media:**

- Quantities of water
- Polyvalent foam
- BC powder
- Carbon dioxide

5.2 Unsuitable extinguishing media:

- None

5.3 Special exposure hazards:

- On heating: release of toxic/combustible gases/vapours: phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
- Gas/vapour spreads at floor level: ignition hazard
- Vapour-air mixture is flammable/explosive within the explosion limits
- Aerosol may explode under the effect of heat

5.4 Instructions:

- Dilute toxic gases with water spray
- Do not move the load if exposed to heat

5.5 Special protective equipment for firefighters:

- Heat/fire exposure: compressed air/oxygen apparatus
-

6. Accidental Release Measures**6.1 Personal protection/precautions:**

See heading 8.1/8.3/10.3

6.2 Environmental precautions:

- Use appropriate containment to avoid environmental contamination

6.3 Methods of cleaning up:

- Allow product to solidify and remove it by mechanical means
 - Remove uncured foam with acetone
-

7 Handling and Storage**7.1 Handling:**

- Observe very strict hygiene - avoid contact
- In case of insufficient ventilation: keep naked flames/sparks away
- Remove contaminated clothing immediately/reinigen

7.2 Storage:

- Keep out of direct sunlight
- Keep away from: heat sources, ignition sources, acids, bases

Storage temperature : < 50 °C

Quantity limit : N.D. kg

Storage life : 365 days

7.3 Specific uses:

- See information supplied by the manufacturer

8. Exposure Limits and personal Protection

8.1 Exposure limit values:

POLYMETHYLENEPOLYPHENYLISOCYANATE:

TLV-TWA : - mg/m³ - ppm

TLV-STEL : - mg/m³ - ppm

TLV-Ceiling : - mg/m³ - ppm

MEL-LTEL : 0.02 (-NCO) mg/m³ - ppm

MEL-STEL : 0.07 (-NCO) mg/m³ - ppm

MAK : - mg/m³ - ppm

TRK : - mg/m³ - ppm

MAC-TGG 8 h : - mg/m³

MAC-TGG 15 min. : - mg/m³

MAC-Ceiling : - mg/m³

VME-8 h : - mg/m³ - ppm

VLE-15 min. : - mg/m³ - ppm

GWBB-8 h : - mg/m³ - ppm

GWK-15 min. : - mg/m³ - ppm

Momentary value : - mg/m³ - ppm

EC : - mg/m³ - ppm

EC-STEL : - mg/m³ - ppm

ISOBUTANE:

TLV-TWA : - mg/m³ - ppm

TLV-STEL : - mg/m³ - ppm

TLV-Ceiling : - mg/m³ - ppm

OES-LTEL : - mg/m³ - ppm

OES-STEL : - mg/m³ - ppm

MAK : 2400 mg/m³ 1000 ppm

TRK : - mg/m³ - ppm

MAC-TGG 8 h : - mg/m³

MAC-TGG 15 min. : - mg/m³

MAC-Ceiling : - mg/m³

VME-8 h : - mg/m³ - ppm

VLE-15 min. : - mg/m³ - ppm

GWBB-8 h : - mg/m³ - ppm

GWK-15 min. : - mg/m³ - ppm

Momentary value : - mg/m³ - ppm

EC : - mg/m³ - ppm

EC-STEL : - mg/m³ - ppm

DIMETHYL ETHER:

TLV-TWA : - mg/m³ - ppm

TLV-STEL : - mg/m³ - ppm

TLV-Ceiling : - mg/m³ - ppm

OES-LTEL : - mg/m³ 400 ppm

OES-STEL : - mg/m³ 500 ppm

MAK : 1900 mg/m³ 1000 ppm

TRK : - mg/m³ - ppm

MAC-TGG 8 h : 950 mg/m³

MAC-TGG 15 min. : 1500 mg/m³

MAC-Ceiling : - mg/m³

VME-8 h : - mg/m³ - ppm
VLE-15 min. : - mg/m³ - ppm
GWBB-8 h : - mg/m³ - ppm
GWK-15 min. : - mg/m³ - ppm
Momentary value : - mg/m³ - ppm
EC : 1920 mg/m³ 1000 ppm
EC-STEL : - mg/m³ - ppm
PROPANE:
TLV-TWA : - mg/m³ 2500 ppm
TLV-STEL : - mg/m³ - ppm
TLV-Ceiling : - mg/m³ - ppm
OES-LTEL : - mg/m³ - ppm
OES-STEL : - mg/m³ - ppm
MAK : 1800 mg/m³ 1000 ppm
TRK : - mg/m³ - ppm
MAC-TGG 8 h : - mg/m³
MAC-TGG 15 min. : - mg/m³
MAC-Ceiling : - mg/m³
VME-8 h : - mg/m³ - ppm
VLE-15 min. : - mg/m³ - ppm
GWBB-8 h : - mg/m³ - ppm
GWK-15 min. : - mg/m³ - ppm
Momentary value : - mg/m³ - ppm
EC : - mg/m³ - ppm
EC-STEL : - mg/m³ - ppm
Printing date : 11-2005 5/11

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- In case of insufficient ventilation: gas mask with filter type A

8.3.2 hand protection:

- Gloves

8.3.3 eye protection:

- Protective goggles

8.3.4 skin protection:

- Protective clothing

9 Physical and Chemical Properties

9.1 General information:

Appearance (at 20°C) : Aerosol

Odour : Characteristic

Colour : Variable in colour

9.2 Important health, safety and environmental information:

pH value : N.D.

Boiling point/boiling range : N.D. °C

Flashpoint : Contains extremely flammable components

Explosion limits : N.D. vol%

Vapour pressure (at 20°C) : N.D. hPa

Vapour pressure (at 50°C) : N.D. hPa
Relative density (at 20°C) : N.D.
Water solubility : Insoluble
Soluble in : N.D.
Relative vapour density : N.D.
Viscosity : N.D. Pa.s
Partition coefficient n-octanol/water : N.D.
Evaporation rate
ratio to butyl acetate : N.D.
ratio to ether : N.D.

9.3 Other information:

Melting point/melting range : N.D. °C
Auto-ignition point : N.D. °C
Saturation concentration : N.D. g/m³

10 Stability and Reactivity**10.1 Conditions to avoid/reactivity:**

- Unstable on exposure to heat

10.2 Materials to avoid:

- Heat sources, ignition sources, acids, bases

10.3 Hazardous decomposition products:

- May polymerize on exposure to temperature rise
- On heating: release of toxic/combustible gases/vapours: hydrogen cyanide
- On heating: release of toxic/combustible gases/vapours: phosphorus oxides,
nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
- May polymerize with many compounds e.g.: (strong) bases and amines
- Reacts violently with (some) acids/bases

11. Toxicological Information**11.1 Acute toxicity:**

POLYMETHYLENEPOLYPHENYLISOCYANATE:

LD50 oral rat : > 10000 mg/kg

LD50 dermal rabbit : N.D. mg/kg

LD50 dermal rabbit : > 5000 mg/kg

LC50 inhalation rat : N.D. mg/1/4 h

LC50 inhalation rat : N.D. ppm/4 h

alpha, alpha', alpha''-1,2,3-PROPANETRIYL-tris(omega-HYDROXY-)

POLY[OXY(METHYL-1,2-

ETHANEDIYL)] :

LD50 oral rat : 1500/2000 mg/kg

LD50 dermal rabbit : N.D. mg/kg

LD50 dermal rabbit : > 2000 mg/kg

LC50 inhalation rat : N.D. mg/1/4 h

LC50 inhalation rat : N.D. ppm/4 h

ISOBUTANE:

LD50 oral rat : N.D. mg/kg

LD50 dermal rabbit : N.D. mg/kg

LD50 dermal rabbit : N.D. mg/kg

LC50 inhalation rat : 658 mg/1/4 h

LC50 inhalation rat : N.D. ppm/4 h

PROPANE:

LD50 oral rat : N.D. mg/kg

LD50 dermal rabbit : N.D. mg/kg
LD50 dermal rabbit : N.D. mg/kg
LC50 inhalation rat : 513 mg/l/4 h
LC50 inhalation rat : 280000 ppm/4 h

11.2 Chronic toxicity:

POLYMETHYLENEPOLYPHENYLISOCYANATE:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed
Carcinogenicity (TLV) : not listed
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed
Carcinogenicity (MAK) : 3B
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : -
IARC classification : 3

DIMETHYL ETHER:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed
Carcinogenicity (TLV) : not listed
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed
Carcinogenicity (MAK) : not listed
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : D
IARC classification : not listed

11.3 Routes of exposure: inhalation, eyes and skin**11.4 Acute effects/symptoms (upon overexposure) :****AFTER INHALATION:**

- Dry/sore throat
- Coughing
- Irritation of the respiratory tract
- Irritation of the nasal mucous membranes
- Runny nose

FOLLOWING SYMPTOMS MAY APPEAR LATER:

- Inflammation of the respiratory tract
- Risk of lung oedema
- Respiratory difficulties

AFTER SKIN CONTACT:

- Tingling/irritation of the skin

AFTER EYE CONTACT:

- Irritation of the eye tissue
 - Lacrimation

11.5 Chronic effects:

- May cause sensitization by skin contact

- May cause sensitization by inhalation
- Contains substance with uncertain carcinogenic properties (polymethylenepolyphenylisocyanate)

ON CONTINUOUS EXPOSURE/CONTACT:

- Body temperature rise
- Tremor
- Feeling of weakness
- Headache
- Skin rash/inflammation
- May stain the skin
- Dry skin
- Risk of pneumonia

12 Ecological Information**12.1 Ecotoxicity:**

- No data available

12.2 Mobility:

- **Volatile organic compounds (VOC):** 18 %
- For other physicochemical properties see section 9

12.3 Persistence and degradability:

- **biodegradation BOD₅ :** N.D. % ThOD
- **water :** No data available
- **soil : T_{1/2}:** N.D. days

12.4 Bioaccumulative potential:

- **log P_{ow} :** N.D.
- **BCF :** N.D.

12.5 Other adverse effects:

- **WGK :** - (classification in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- **Effect on the ozone layer :** Not dangerous for the ozone layer (1999/45/EC)
- **Greenhouse effect :** No data available
 - **Effect on waste water purification :** No data available

13 Disposal Considerations**13.1 Provisions relating to waste:**

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 05 01* (waste isocyanates)
- Hazardous waste (91/689/EEC)

13.2 Disposal methods:

- Specific treatment

13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10* (packaging containing residues of or contaminated by dangerous substances)

14. Transport Information

14.1 Classification of the substance in compliance with UN**Recommendations**

UN-number : 1950

CLASS : 2.1

SUB RISKS : -

PACKING : -

PROPER SHIPPING NAME :

UN 1950, Aerosols

14.2 ADR (transport by road)

CLASS : 2

CLASSIFICATION CODE : 5 F

DANGER LABEL TANKS : -

DANGER LABEL PACKAGES : 2.1

14.3 RID (transport by rail)

CLASS : 2

CLASSIFICATION CODE : 5 F

DANGER LABEL TANKS : -

DANGER LABEL PACKAGES : 2.1

14.4 ADNR (transport by inland waterways)

CLASS : 2

CLASSIFICATION CODE : 5 F

DANGER LABEL TANKS : -

DANGER LABEL PACKAGES : 2.1

14.5 IMDG (maritime transport)

CLASS : 2.1

SUB RISKS : -

PACKING : -

MFAG : -

EMS : F-D, S-U

MARINE POLLUTANT : -

14.6 ICAO (air transport)

CLASS : 2.1

SUB RISKS : -

PACKING : -

PACKING INSTRUCTIONS PASSENGER AIRCRAFT :

PACKING INSTRUCTIONS CARGO AIRCRAFT :

14.7 Special precautions in connection with transport

: none

14.8 Limited quantities (LQ) :

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4, **only** the following prescriptions shall be complied with:

each package shall display a diamond-shaped figure with the following inscription:

- 'UN 1950'

or, in the case of different goods with different identification numbers

within a single package:

- the letters 'LQ'

15. Regulatory Information

Labelling in accordance with directives 67/548/EEC and 1999/45/EC

Contains : polymethylenepolyphenylisocyanate

R20 : Harmful by inhalation

R36/37/38 : Irritating to eyes, respiratory system and skin

R42/43 : May cause sensitization by inhalation and skin contact

S23 : Do not breathe spray

S36/37/39 : Wear suitable protective clothing gloves, and eye/face protection

S38 : In case of insufficient ventilation, wear respiratory equipment

S45 : In case of accident or if you feel unwell, seek medical advice (show the label where possible)

S51 : Use only in well ventilated area

Keep away from sources of ignition - No smoking.

Keep out of reach of children.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn after use.

Do not spray on a naked flame or any incandescent material

Contains isocyanates. See information supplied by the manufacturer.

16. Other Information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE

N.D. = NOT DETERMINED

***** = INTERNAL CLASSIFICATION

Full text of any R-phrases referred to under heading 2:

R12 : Extremely flammable

R20 : Harmful by inhalation

R22 : Harmful if swallowed

R36/37/38 : Irritating to eyes, respiratory system and skin

R42/43 : May cause sensitization by inhalation and skin contact

R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Exposure limits:

TLV : Threshold Limit Value - ACGIH US 2000

OES : Occupational Exposure Standards - United Kingdom 1999

MEL : Maximum Exposure Limits - United Kingdom 1999

MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001

TRK : Technische Richtkonzentrationen - Germany 2001

MAC : Maximale aanvaarde concentratie - the Netherlands 2002

VME : Valeurs limites de Moyenne d'Exposition - France 1999
VLE : Valeurs limites d'Exposition à court terme - France 1999
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 1998
GWK : Grenswaarde kortstondige blootstelling - Belgium 1998
EC : Indicative occupational exposure limit values - directive 2000/39/EC
I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit
a: aerosol **r**: rook/Rauch (fume)
d: damp (vapour) **st**: stof/Staub (dust)
du: dust **ve**: vezel (fibre)
fa: Faser (fibre) **va**: vapour
fi: fibre **om**: oil mist
fu: fume **on**: olienevel/Ölnebel (oil mist)
p: poussière (dust) **part**: particles
Chronic toxicity:
K : List of the carcinogenic substances and processes - the Netherlands 2002

October 20, 2006.